


# PFM-540I Rev.B

## PC/104 CPU Module with AMD Geode™ LX Processor



### Features

- Onboard AMD Geode™ LX800 Processor
- AMD LX800 + CS5536
- SODIMM x 1, DDR333 Up to 1 GB, DDR400 Up to 512MB
- 10/100Base-TX Ethernet x 1
- 18/24-bit TTL LCD Support
- EIDE x 1, CompactFlash™ x 1
- USB 2.0 x 4, COM x 4 and Parallel x 1
- PC/104 Socket
- +5V Only Operation, AT Power Type
- Low Power Consumption



### Specifications

System	
Form Factor	PC/104
Processor	Onboard AMD Geode™ LX800 Processor 500MHz
System Memory	200-pin DDR SODIMM x 1, Max 1GB for DDR333 and 512MB for DDR400
Chipset	AMD LX800 + CS5536
I/O Chipset	SMSC 3114-Nu
Ethernet	Intel® 82551ER, 10/100Base-TX
BIOS	Award 1MB FLASH ROM
Watchdog Timer	Generates a time-out system reset
H/W Status Monitoring	Supports power supply voltages and temperature monitoring
Expansion Interface	PC/104 socket x 1
Power Requirement	+5V/AT
Power Consumption (Typical)	AMD Geode™ LX800 500MHz, DDR400 512MB +5V@1.53A
Battery	Lithium battery
Board Size	3.55" (L) x 3.775" (W) (90mm x 96mm)
Gross Weight	0.25 lb (0.11 kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	100,000
Display	
Supports CRT/ LCD simultaneous display	
Chipset	AMD LX800
Memory	Shared system memory up to 254 MB
Resolutions	Up to 1600 x 1200 @ 32bpp for CRT Up to 1024 x 768 @ 24bpp for LCD
LCD Interface	18/24-bit TTL TFT LCD
I/O	
Storage	EIDE x 1 (UDMA 33 for one device), Type I CompactFlash™ x 1
Serial Port	RS-232 x 3, RS-232/422/485 x 1
Parallel Port	SPP/ EPP/ ECP mode
USB	USB2.0 x 4
PS/2 Port	Keyboard + Mouse x 1

### Packing List

- **9681540I02**  
Cable Kit for PFM-540I Rev.B
  - 1701440350 44-pin IDE Cable x 1
  - 1700060152 Keyboard & Mouse Cable x 1
  - 1709100201 USB Cable x 1
  - 1701160201 VGA Cable x 1
- Quick Installation Guide
- Utility CD
- PFM-540I Rev.B

### Ordering Information

- **TF-PFM-540I-B10 (Fanless)**  
PC/104 Board, AMD LX800 LCD, DDR, LAN, 4 COM, 4 USB, CompactFlash™, PC/104, AT, Rev. B1.0

### Optional Accessories

- **1701100207**  
RS-232 Cable x 1
- **1700100200**  
LAN Cable x 1
- **1701260200**  
Printer Cable x 1
- **1709100201**  
USB Cable x 1