

FOX-15R

15" XGA Heavy-Duty Touch Display With Remote Display Technology

07

Industrial Remote Touch Display Solutions



Features

- Supports Remote Display Technology
- IP-67 Water-Proof & Marine IEC60945 ed.4 Compliant
- 15" 250 Nits XGA LED Backlight (FOX-15R-HTT)
15" 800 Nits XGA LED Backlight (FOX-15R-STT)
- Anti-Fog Design: LCD+ TS Bonding Technology
- Backlight On/Off & Brightness Adjustment

CE FC

Ordering Information

- TBD

Optional Accessories

- TBD

Specifications

System	
Input Signal	VGA
On Screen Display Control	Brightness, Contrast, Phase, Sharpness, AutoTune, H/V-position
I/O connector	RJ-45 x 2
OS support	Windows® XP, Windows® 7, Linux Fedora
Mechanical	
Construction	IP-67 Sealed Aluminum Alloy Chassis
Mounting	VESA 75/100
Dimension	—
Carton Dimension	—
Gross Weight	—
Net Weight	—
Environmental	
Operating Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Storage Temperature	-22°F ~ 158°F (-30°C ~ 70°C)
Storage Humidity	10%~95% @ 40°C; non-condensing
Vibration	1 g rms/ 5~500Hz/ Random operation
Shock	15 G peak acceleration (11 msec. Duration)
EMC	CE/FCC Class A IEC 60945 ed.4
Power Supply	
DC input	DC 9~30V
LCD	
Display type	15" TFT-LCD
Max Resolution	1024x768
Max. Colors	262K colors
Luminance	HTT : 250 nits, STT : 800 nits
Viewing Angle	HTT :170°(H)/160°(V),STT :160°(H)/140°(V)
Back Light	HTT: CCFL, STT: LED
Back Light MTBF (hours)	HTT: 30,000, STT: 60,000
Touchscreen	
Type	5-wire resistive
Light Transmission	80%
Lifetime (times)	35 million activations

- Note: Users have to select the ACG-203 to work with the FOX-15R.